

Shanghai Luqing Rubber Co., Ltd

Tech Care Industry Company Limited

OneCoin Brand Radial OTR Tire Specs

Contacts: Thomson Chi

Add: 12F Shandong International Trade Mansion,
51 Taiping Road, Qingdao, China 266071

Tel: 0086-532-8297-2856

Fax: 0086-532-8297-2857

Hp: 00866-139-6988-4990

Website: www.otrtyre.com

www.monolithtyre.com

Email: thomsonchi@gmail.com

monolithotr@gmail.com



HKI

- ◆ For dump truck, loader and bulldozer, be used in mining and construction application.
- ◆ Aggressive tread block provides excellent stability and cut resistance.
- ◆ Special tread compound offers premium abrasion resistance and chunking resistance performance.
- ◆ Unique carcass material provides the best load capacity.
- ◆ Special lug groove together with super-square tread gives top grip capability and excellent traction performance.

Applicable types of vehicles:



Tire Size	Star Rating	Tread Pattern		Load Index	Tube Type	Rim & Flange Size	Inflated Tire Dimensions (mm)		Max Load Capacity (kg)		Inflation Pressure (kPa)	
		Tread Code	TRA Code				OD±1.5%	SW±3.5%	10km/h	50km/h	10km/h	50km/h
17.5R25	★	HKI	E3/L3/G3	176/157	TBLS	14.00/1.5	1348	445	7100	4125	500	375
	★★	HKI	E3/L3/G3	182/167			1348	445	8500	5450	650	525
20.5R25	★	HKI	E3/L3/G3	186/168	TBLS	17.00/2.0	1493	521	9500	5600	500	375
	★★	HKI	E3/L3/G3	193/177			1493	521	11500	7300	650	525
23.5R25	★	HKI	E3/L3/G3	195/176	TBLS	19.50/2.5	1617	597	12150	7100	500	375
	★★	HKI	E3/L3/G3	201/185			1617	597	14500	9250	650	525
26.5R25	★	HKI	E3/L3/G3	202/184	TBLS	22.00/3.0	1750	673	15000	9000	500	375
	★★	HKI	E3/L3/G3	209/193			1750	673	18500	11500	650	525
29.5R25	★	HKI	E3/L3/G3	208/191	TBLS	25.00/3.5	1874	749	18000	10900	500	375
	★★	HKI	E3/L3/G3	216/200			1874	749	22400	14000	650	525



SHDLS

- ◆ Special cut resistance; long tread life.
- ◆ Enhanced stability and riding comfort with good traction on rough road.
- ◆ Robust carcass design make all application service tyre.
- ◆ Unique sidewall design provides super cut-resistance.
- ◆ Suitable for stone pit, industry zone and underground mine

Applicable types of vehicles:



Tire Size	Star Rating	Tread Pattern		Load Index	Tube Type	Rim & Flange Size	Inflation Dimensions(mm)		Max Load Capacity(kg)		Inflation Pressure(kPa)	
		Tread Code	TRA Code				OD±1.5%	SW±3.5%	10km/h	50km/h	10km/h	50km/h
20.5R25	★★	SHDLS	L5	193/177	TBLS	17.00/2.0	1548	520	11500	7300	575	450
23.5R25	★★	SHDLS	L5	201/185	TBLS	19.50/2.5	1673	597	14500	9250	575	450
26.5R25	★★	SHDLS	L5	209/193	TBLS	22.00/3.0	1798	673	18500	11500	575	450
29.5R25	★★	SHDLS	L5	216/200	TBLS	25.00/3.5	1921	750	22400	14000	575	450
35/65R33	★★	SHDLS	L5	223/207	TBLS	28.00/3.5	2077	889	27250	17500	650	475



SHRSM

- ◆ Smooth tread pattern; special cut resistance and loading capability.
- ◆ Extra deep tread design gives excellent wear performance and long service life.
- ◆ Special compound minimizes the inner heating-up and maximizes cut & chunking resistance.
- ◆ Reliable in the most extreme harsh conditions; suitable for stone pit, industry zone and underground mine.

Applicable types of vehicles:



Tire Size	Star Rating	Tread Pattern		Load Index	Tube Type	Rim & Flange Size	Inflation Dimensions(mm)		Max Load Capacity(kg)		Inflation Pressure(kPa)	
		Tread Code	TRA Code				OD±1.5%	SW±3.5%	10km/h	50km/h	10km/h	50km/h
17.00R25	★★	SHRSM	L5S	182/167	TBLS	14.00/1.5	1399	445	8500	5450	575	450
18.00R25	★★	SHRSM	L5S	204/185	TBLS	13.00/2.5	1673	498	16000	9250	825	700
23.5R25	★★	SHRSM	L5S	201/185	TBLS	19.50/2.5	1673	597	14500	9250	575	450
26.5R25	★★	SHRSM	L5S	209/193	TBLS	22.00/3.0	1798	673	18500	11500	575	450
29.5R25	★★	SHRSM	L5S	218/202	TBLS	25.00/3.5	2023	750	23600	15000	575	450



HK298

- ◆ For dump truck application.
- ◆ Aggressive tread block provides excellent stability and grip capability.
- ◆ Unique tread compound offers best abrasion resistance and chunking resistance.
- ◆ Maximized land ratio gives maximum grip capability and traction performance.

Applicable types of vehicles:



Tire Size	Star Rating	Tread Pattern		Load Index	Tube Type	Rim & Flange Size	Inflation Dimensions(mm)		Max Load Capacity(kg)		Inflation Pressure(kPa)	
		Tread Code	TRA Code				OD±1.5%	SW±3.5%	10km/h	50km/h	10km/h	50km/h
37.00R57	★★	HK298	E4	261/245	TL	27.00/6.0	3438	1016	82500	51500	825	700
40.00R57	★★	HK298	E4	268/250	TL	29.00/6.0	3594	1097	100000	60000	825	700



HK208

- ◆ For dump truck application.
- ◆ Aggressive tread block provides excellent stability and grip capability, the approved stress distribution minimizes shoulder and sidewall separation.
- ◆ Unique tread compound offers best abrasion resistance and chunking resistance.
- ◆ Unique carcass material provides the best load capacity

Applicable types of vehicles:



Tire Size	Star Rating	Tread Pattern		Load Index	Tube Type	Rim & Flange Size	Inflation Dimensions(mm)		Max Load Capacity(kg)		Inflation Pressure(kPa)	
		Tread Code	TRA Code				OD±1.5%	SW±3.5%	10km/h	50km/h	10km/h	50km/h
21.00R35	★	HK208	E4	208/190	TBLS	15.00/3.0	2052	572	18000	10600	550	475
	★★	HK208		219/201					24300	14500	825	700
24.00R35	★★	HK208	E4	227/209	TBLS	17.00/3.5	2175	653	30750	18500	825	700